

BÜFA®-INDUSTRY-GELCOAT 2.0

Gelcoat

Industry Gelcoat with top Price-Performance Ratio!



BÜFA®-INDUSTRY-GELCOAT 2.0

As Europe's leading supplier, BÜFA continuously invests in the further development of its product range. Of particular importance are good processing properties that save time, materials and working operations.

BÜFA®-Industry Gelcoat 2.0 is a pre-accelerated gelcoat in a spraying consistence. This convincing, reliable industry gelcoat can be used for a wide range of applications for components that are used indoors as well as outdoors (technical parts, machine covers, furniture, etc.). BÜFA®-Industry Gelcoat 2.0 gives fibre reinforced components a high quality surface. This new generation of gelcoat has the best processing properties.



TINT IT YOURSELF WITH "BÜFA®-PIGMENT PASTES":

The Article 669-0002 is an unpigmented, coloured gelcoat that can be tinted with an appropriate BÜFA®-Pigment Paste. Users can mix the quantities they need themselves.

04-19 | image sources: AdobeStock 43756974 © vetkit, AdobeStock 170723767 © VanderWolf Images, AdobeStock 236117184 © sidorovstock
The above information is based on our present knowledge and experience. In view of the many possible influences during the use and application of our products, this information does not relieve the user from the need to conduct his/her own tests and experiments. No legally binding warranty of certain properties or of suitability for a certain purpose can be derived from these specifications. It is the responsibility of the recipient or processor of our products to ensure that any proprietary rights and existing laws and legislation are observed. The current version of the relevant EU Safety Data Sheet should also be complied with.
Technical datasheets and information can be found under buefa.de

PRODUCT ADVANTAGES:

- Good price/performance ratio
- Good flexibility and little brittleness
- Very processing-friendly


RECOMMENDATION FOR BÜFA MACHINES:

- BÜFA®-Tec GSU ES1 „Easy Lift“
- BÜFA®-Tec Delta EVO-LINE
- BÜFA®-Tec Sigma 6 EVO-LINE

PROCESSING METHOD: Spray processes (S)

PRODUCTION METHOD: Batchwise

AVAILABLE COLOURS:




669-0002
natural / unpigmented



669-7085
light grey similar
to RAL 7035*



* according to
the BÜFA method



669-0510
white similar
to RAL 9010*

If there is larger order volume, other selected shades of colour are also available. Please get in touch with us for this.

BÜFA

Composites

BÜFA Composite Systems GmbH & Co. KG
Hohe Looge 2-8
26180 Rastede
GERMANY

Phone +49 4402 975-0
Fax +49 4402 975-300
compositesystems@buefa.de
buefa.de

A member of the BÜFA Group